

RESILIENT TYRES - COMFORT XT+

Tyre Size	Rim Size	EASY FIT/ NORMAL	Tread pattern {Smooth(SM)/ Traction(TR)/Rib(R)} {APP-Aperture}	Tyre Dimension				Load Capacity (kg)						Finished tyre weight (kg)	Pcs/20ft
				Inch		mm		Counterbalanced lift Trucks		Other Vehicles (Trailers)			Static		
				Max Width	O.D.+/- 2%	Max Width	O.D.+/- 2%	Load Wheels up to 25Km/h	Steering Wheels	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h	0 km/h		
6.00 - 9	4.00E - 9	EF/N	TR APP	5.4	20.9	136	530	1695	1305	1695	1540	1305	1970	25.40	640
6.50 - 10	5.00F - 10	EF/N	TR APP	6.3	22.6	160	573	2100	1620	2100	1910	1620	1440	34.70	480
7.00 - 12	5.00S - 12	EF/N	TR APP	6.7	26.0	170	660	2620	2010	2620	2380	2010	3040	47.00	320
28x9 - 15	7.00 - 15	EF/N	TR APP	8.5	27.3	216	694	3390	2610	3390	3075	2610	3940	60.20	264
12.00 - 24	8.50 - 24	N	TR APP	11.2	46.5	285	1180	7235	6030	7235	6575	6030	9100	251.90	64