

RESILIENT TYRES - SKS

Tyre Size	Rim Size	EASY FIT/ NORMAL	Tread Pattern {Smooth(SM)/ Traction(TR)/ Rib(R)} {APP - Aperture } (ND- Non Directional)	Tyre Dimension				Load Capacity (kg)			Finished tyre weight(kg)	Pcs/20ft
				Inch		mm		Other Vehicles (Trailers)				
				Max Width	O.D.+/-2%	Max Width	O.D.+/-2%	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h		
110/75 - 6	3.00 - 6	N	RIB LUG	4.3	12.2	108	311	850	755	630	5.90	2500
5.70 - 12	4.00 - 12	N	SKS - APP 2FA	5.7	22	144	560	1755	1595	1352	22.00	600
30x10 - 16	6.00G - 16	N	SKS - APP 2FA	9.1	29.4	233	746	3300	3006	2525	67.50	210
31x10 - 20	7.50 - 20	EF/N	SKS - APP 1FA	9.4	30.9	238.5	785	3600	3273	2975	63.00	120
31x10 - 20	7.50 - 20	EF/N	SKS	9.4	30.9	238.5	785	4235	3850	3500	64.00	120
33x12 - 20	7.50 - 20	EF/N	SKS	11.3	32.9	288	837	5920	5390	4900	91.50	110
33x12 - 20	8.00 - 20	EF/N	SKS	11.3	32.9	288	837	5920	5390	4900	92.90	110
33x12 - 20	7.50 - 20	EF/N	SKS - APP 1FA	11.3	32.9	288	837	5032	4582	4165	90.50	110
33x12 - 20	8.00 - 20	EF/N	SKS - APP 1FA	11.3	32.9	288	837	5032	4582	4165	91.50	110
33x12 - 20	7.50 - 20	EF/N	SKS - APP 2FA	11.3	32.9	288	837	4529	4124	3749	89.00	110
33x12 - 20	8.00 - 20	EF/N	SKS - APP 2FA	11.3	32.9	288	837	4529	4124	3749	91.20	110
33x12 - 20	7.50 - 20	EF/N	SM	11.3	32.9	288	837	5920	5390	4900	102.20	110
33x12 - 20	8.00 - 20	EF/N	SM	11.3	32.9	288	837	5920	5390	4900	103.20	110
33x12 - 20	7.50 - 20	EF/N	SM - APP 1FA	11.3	32.9	288	837	5032	4582	4165	100.50	110
33x12 - 20	8.00 - 20	EF/N	SM - APP 1FA	11.3	32.9	288	837	5032	4582	4165	101.50	110
33x12 - 20	7.50 - 20	EF/N	SM - APP 2FA	11.3	32.9	288	837	4529	4124	3749	99.60	110
33x12 - 20	8.00 - 20	EF/N	SM - APP 2FA	11.3	32.9	288	837	4529	4124	3749	100.60	110
34x10 - 20	7.50 - 20	EF/N	ND - SKS - APP 1FA	9.9	33.7	252	855	5032	4582	4165	92.80	108
36x12 - 20	7.50 - 20	N	SKS - APP 2FA	12.0	36.2	305	919	4800	4400	4000	120.50	84
36x12 - 20	8.00 - 20	N	SKS - APP 2FA	12.0	36.2	305	919	4800	4400	4000	122.00	84
36x14 - 20	7.50 - 20	N	SKS - APP 2FA	14	36.2	355.6	919.5	6175	5605	4750	140.00	84