

RESILIENT TYRES - SMOOTH

Tyre Size	Rim Size	EASY FIT/ NORMAL	Tread Pattern {Smooth(SM)/ Traction(TR)/ Rib(R)}	Tyre Dimension				Load Capacity (kg)						Finished tyre weight (kg)	Pcs/20ft
				Inch		mm		Counter balanced lift Trucks		Other Vehicles (Trailers)			Static		
				Max Width	O.D.+/- 2%	Max Width	O.D.+/- 2%	Load Wheels	Steering Wheels	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h	0 km/h		
12 x 31/2 - 8	3.00D - 8	N	SM	3.9	12.0	98.5	306	780	600	780	700	600		4.70	
15 x 41/2 - 8 (125/75-8)	3.00D - 8	EF/N	SM	4.4	14.8	111	376	1040	800	1040	945	800	1210	9.40	1600
17 x 7 - 8	4.33R - 8	EF/N	SM	5.8	16.8	148	427	1860	1430	1860	1685	1425	2160	17.80	910
5.00 - 8	3.00D - 8	EF/N	SM	4.7	18.0	120	457	1415	1090	1415	1285	1090	1645	14.25	1100
6.50 - 10	5.00F - 10	EF/N	SM	6.3	22.6	155	570	2340	1800	2340	2125	1800	2720	36.30	480
7.50 - 16	6.00 - 16	N	SM	8.2	31.5	208	800	3950	3050	3950	3600	3050	4605	82.00	154
8.25 - 16	6.00 - 16	N	SM	8.2	32.2	208	818	3950	3050	3950	3600	3050	4605	85.60	154
10.00 - 20	7.50 - 20	N	SM	9.7	40.2	247	1020	6000	5000	6000	5450	5000	7550	180.00	90