

DUAL ASSEMBLY - XT

Tyre Size	Rim Size	EASY FIT /Normal	Tread Pattern {Smooth (SM) / Traction (TR) / Rib	Tyre Dimension				Load Capacity (kg)							Finishe d tyre weight (kg)	Pcs/20ft
				Inch		mm		Counter balanced lift Trucks		Other Vehicles (Trailers)			Static			
				Max Width	O.D.+/- 2%	Max Width	O.D.+/- 2%	Load Wheels	Steering Wheels	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h	0 km/h			
9.00-20	7.00-20	N	TR	9.0	39.0	229	990	5400	4500	5400	4905	4500	6795	123.00	100	
10.00 - 20	7.00 - 20	N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	173.20	90	
10.00 - 20	7.50 - 20	EF/N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	175.60	90	
10.00 - 20	8.00-20	N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	177.80	90	
11.00 - 20	7.00 - 20	N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	173.20	90	
11.00-20	7.50 - 20	EF/N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	175.60	90	
11.00 - 20	8.00-20	N	TR	9.9	41.1	251	1045	6000	5000	6000	5450	5000	7550	177.80	90	
12.00 - 20	8.0 - 20	N	TR	11.2	43.2	285	1098	7500	6300	7560	6885	6300	9515	211.00	70	
12.00 - 20	8.5 - 20	N	TR	11.2	43.2	285	1098	7500	6300	7500	6885	6300	9515	212.00	70	

DUAL ASSEMBLY- OPTIMA

Tyre Size	Rim Size	EASY FIT /Normal	Tread Pattern {Smooth (SM) / Traction (TR) / Rib	Tyre Dimension				Load Capacity (kg)							Finishe d tyre weight (kg)	Pcs/20ft
				Inch		mm		Counter balanced lift Trucks		Other Vehicles (Trailers)			Static			
				Max Width	O.D.+/- 2%	Max Width	O.D.+/- 2%	Load Wheels	Steering Wheels	Up to 6Km/h	Up to 10Km/h	Up to 25Km/h	0 km/h			
10.00 - 20	7.50 - 20	EF/N	TR	9.8	40.8	248	1036	6000	5000	6000	5450	5000	7550	151.7	90	
10.00 - 20	8.00 - 20	EF/N	TR	9.8	40.8	248	1036	6000	5000	6000	5450	5000	7550	152.7	90	